

HTML Reference Sheet

<code><!--</code>	Comments
<code>// --!></code>	End of Comments
<code><html></code>	Goes at beginning of HTML document
<code></html></code>	Goes at end of HTML document
<code><head></code>	Marks beginning of head section of the HTML document
<code></head></code>	Marks end of head section of the HTML document
<code><body></code>	Marks beginning of the body section of the HTML document
<code></body></code>	Marks end of the body section of the HTML document
<code><h1>...</h1></code>	Surrounds a first level heading
<code><h2>...</h2></code>	Surrounds a second level heading
<code><h3>...</h3></code>	Surrounds a third level heading
<code><h4>...</h4></code>	Surrounds a fourth level heading
<code><h5>...</h5></code>	Surrounds a fifth level heading
<code><h6>...</h6></code>	Surrounds a sixth level heading
<code><title>...</title></code>	Surrounds the title of the document. This does not appear in the document when displayed on browser. This is used only in head section.
<code><p> </p></code>	Used to mark the beginning or end of a paragraph. Normally only one is used.
<code><a> </code>	Creates a link to another document or to an anchor within the current document. Attributes that may be used with it: <code>href="..."</code> The URL of a document you are linking to. <code>name="..."</code> The name of an anchor in the document that href can reference to.
<code>...</code>	Creates an ordered list. <code></code> marks each item. Attributes that may be used with it: <code>type="..."</code> Netscape- Type of numbers on the list. (A, a, I, i, 1)
<code>...</code>	Creates an unordered list – features bullets. <code></code> marks each item. Attributes that may be used with it: <code>type="..."</code> Netscape- Type of bullets on the list. (disc, circle, square)
<code><menu>...</menu></code>	A menu list of items. <code></code> marks each item.
<code> </code>	surrounds each item in an ordered or unordered list or a menu.
<code>...</code>	Sets emphasis usually in italic
<code>...</code>	Stronger emphasis than <code></code> . Usually in bold.

`...` Puts font in bold.

`<i>...</i>` Puts font in italic.

`<hr />` Draws a horizontal line across page

`
` Produces a line break.

`<center>...</center>` Centers text

`...` Changes the size of the font.

Attributes that may be used with it:

`Size='...'` The size of the font from 1 to 7. Default size is 3. Can also express number after size as + and number to increase size or – and number to decrease size ``

`` Inserts an image in the document

Attributes that may be used with it:

`ISMAP` Uses a clickable image map.

`Src='...'` The URL of the image.

`Alt='...'` Text that will be displayed if the browser cannot display images or the words that will appear when cursor is moved over the image.

`Align='...'` The alignment of the image. (Left, Right, Center)

`Width='...'` The width in pixels of the image.

`Height='...'` The height of the image ion pixels.

Dwight Watt 12/2/97, 2/6/2014